## Capp Rondo

HIGH SPEED MINI-CENTRIFUGE

CAPP APS LANDBRUGSVEJ 10 DK-5260 ODENSE DENMARK

TEL. (+45) 6613 6140 Fax. (+45) 6613 2770

MAIL: INFO@CAPP.DK WEB: WWW.CAPP.DK

Capp Rondo Mini is designed to be an easy-to-use, high performance Mini-centrifuge in a modern and attractive form equipped with maintenance free drive. It enhances the centrifuge product line by offering updated features & benefits.

#### Features & Functions:

Lid lock safety & imbalance detection features ensure utmost safety during operation Unique airflow design - ensures lesser heat generation and lesser noise Quick and convenient setting because of Intuitive simple interface Multiple parameters are displayed at a time on the large back-lit LCD display Brushless DC motor - maintenance free and fit for extended runs Aluminum rotor with capacity of 12 tubes of 1.5 / 2 ml & screw on metal lid

#### Remote Operation & Control:

User can operate through laptop/computer (remote operation) and write up to 99 programs - operation records are saved in Excel sheet. Also, ease in continuing with the last run operation mode due to the last run memory features that controls the Microprocessor.

#### Accessories:

Adaptors are provided for 0.2 and 0.4/0.5 ml tubes - optional 2 x 8 x 0.2 ml strip rotors.

#### Wide range of Applications:

Capp Rondo Mini accelerates up to twelve 1.5/2.0 ml mini-centrifuge tubes to a max speed of 15,000 rpm (rcf: 15,595 x g) enabling to process samples rapidly.

Routine runs, such as spin column preparations can be carried out at your own personalized workstation, with a minimum of time and effort. This compact centrifuge is also cold room & fume hood compatible.

Specifications	CAPP Rondo Mini
Speed setting	500 to 15000 rpm / Min-Sec timer 1 to 999 mins
Maximum Speed RPM / RCF (g)	15000 rpm / 15596 x g
Display	Large Backlit LCD display
Rotor Capacity	12 place Auminum. rotor with metal safety lid for 1.5/2.0 ml microtubes
Motor Type	Brushless DC
Noise Level	< 62 db
Imbalance Detection	Yes
Remote operation	Yes
Robotic integration (Op- tional)	Yes, can be interfaced via USB
Lid Lock Safety	Yes, lid opens automatically on run completion
Dimensions (W x D x H)	230 x 262 x 131 mm
Accessories	Reduction Adaptors for 0.2 / 0.4 ml Microtubes



# Ordering Info

### Capp Rondo

Cat No.	Description
CR-1512	Capp Rondo Mini-centrifuge. 15000rpm/15600g, for 12x 1.5-2.0ml tubes
CR-15-PCR	PCR strip rotor for Capp Rondo CR-1512 w/ reduction adaptors, 1 pc.